



| Number  | Description  | Db |
|---------|--|----|
| AM01078 | Filter House - wall two filters                            | 2  |
| ABE0443 | Suction 2 1/2"-2"  | 4  |
| AKU1892 | Air Regulator - house led lighted V2                       | 2  |
| ACM0860 | Control Panel - IN.K1001                                   | 1  |
| AKU1893 | On-Off tap house 33 transparent V2                         | 1  |
| AKU1891 | Water Diverter 60 - LED lighted V2                         | 1  |
| AKU2101 | Fountain laminar V2  | 6  |
| ACM0874 | Speaker 3" (2 way)   | 2  |
| ACM0874 | Speaker 3" (2 way)   | 2  |
| AJ00249 | Jet 7" - 5 Hole Wellis                                     | 2  |
| AKU1720 | Suction 48   | 2  |
| AJ00169 | Jet - 20 SB - Ozone 90°                                    | 1  |
| AKU2157 | Adapter for swim theter V2                                 | 1  |
| AKU2099 | LED HOUSE V2   | 20 |
| ACM0775 | Control BOX - IN.Y-3                                       | 1  |
| ACM0834 | Circulation pump PCF100 1100 W without prefilter           | 1  |
| ACM0888 | UV-C Stainless steel house set                             | 1  |
| ABE0413 | Turbin hosue   | 1  |
| ACM0857 | Controlbox for turbin                                      | 1  |
| ACM0080 | Spa Pump 3 HP - One Speed                                  | 1  |
| AJ00217 | Jet 3" - transparent 1 Hole Rotation transparent V3 Wellis | 18 |
| AJ00214 | Jet 2" - transparent 1 Hole transparent V3 Wellis          | 6  |
| AF00061 | Pillow 300x126x54 white ribbed                             | 2  |
| ACM0849 | Subwoofer 288W   | 1  |
| ACM0769 | Amplifier - InStream 2                                     | 1  |
| ACM0802 | Led Control Box  | 1  |
| ACM0867 | UV-C control electronics                                   | 1  |
| ACM0901 | Wifi receiver in.touch 2 Gecko EU&UK                       | 1  |
| ACM0881 | In.Grid external heater controller and 4 ways              | 1  |

Product family: SwimLine

|   |   |   |  |        |   |  |
|---|---|---|--|--------|---|--|
| Sheet name: Amazonas - 2019 Turbina                         |   |   | Projection  |        | <br>Wellis Magyarország Zrt. |  |
| File name: FJ_WU00035_ENG_Amazonas-2019_Turbina_úszómedence |   |   |  |        |   |  |
| Dimension SPA: 2350x5500x1470 mm                            |   | Min. electrical needs: 240 V - 35A - 50Hz - 3 kW Heater |  |        |   |  |
| Weight of the SPA: kg                                       |   | Control box: GECKO YE-3 + K1000                         |  |        |   |  |
| Rim height: 150 mm  | Approved by:                                |   | Pr. No: P-00182<br>Fe. No:   |        | Number: WU00035   |  |
| Created: 2019. 09. 27.                                      | Drawer: bato.peter - 2019. 09. 27. 10:36:40 |   | A3   | M 1:20 | page 1 / 3  |  |

Installation instruction

Residual-Current Device (RCD) having a rated operating residual-current not exceeding 30 mA is must

The stated dimensions are for reference only. The actual dimension may be different from the specified

- L: Drain diameter: 50 mm
- E: 3 m cable is required for the electrical connection through the spa skirt.

Cable length/cross section

- Minimum requirement: cable length is maximum 15 m, 3x6 mm2 core flex cable is necessary (230V) - In this case the massage motors and the heating won't work at the same time.
- For full operation: cable length is maximum 15 m, 5x4 mm2 core flex cable is necessary (400V) - In this case the massage motors and the heating work at the same time.

Attention

The hot tube will be installed only if the electrical contractor makes declaration of the installation of Residual-Current Device and proper fuses

Initial installation

The installation or making any repair are allowed only for properly skilled person.  
Disconnecting device has to be installed when the spa is directly connected to the electricity networks.


1. Site preparation

a. Indoor / Basement installation

If you place your spa indoors, be aware of some special requirements: Water may accumulate around the spa, so the flooring mate-rial must have a proper runoff to avoid accumulation of water. When building a new room for the spa, constructing a floor drain is required, or damages may occur due to overflow, overfilling, or technical failure. Our company does not take responsibility for any damage in absence of floor drainage.Humidity will naturally increase in the room where the spa is located and the evaporated water condenses. For this reason ensure that the area has proper ventilation. We recommend installing a dehumidifier in the room.

b. Outdoor and patio installation

A solid horizontal foundation is necessary for installation of the spa. We advise using a reinforced concrete foundation at least 10-15cm thick. Ensure that your deck or foundation will support your spa. You must know the maximal load capacity of the foundation. Consult a qualified building contractor or structural engineer. To find out the weight of your spa, its contents and occupants please refer to the spa specification chart. This weight must not exceed the structure’s rated capacity per square meter, otherwise serious structural damages could result. If you install the spa outdoors, we recommend a reinforced hori-zontal concrete pad at least 10-15cm thick.





Install floor drains around your spa to lead water away even in heavy rain. When constructing the water drain it is advised to form a 10-15cm deep sloping ditch around the spa which directs water to the drain. Water from the drain must be directed to the canal or a drainage with enough capacity.  
**Warning:** Do not expose the spa to direct sunlight (not even empty) without proper coverage. The insulated spa cover preserves the water temperature and provides protection from sunlight and rain. When exposed to sunshine for a longer period it may damage the surface of the spa and the spa equipment. Acrylic rapidly absorbs heat from sun rays, thus reaches a very high surface temperature which may damage the spa. In case of sealed design, if the spa was placed between glass structures, prevent the sun rays from reaching the spa directly through the glass as the temperature may get too high.






c. In-Ground / Sunken Spa

In case of sinking the spa into the ground you must make sufficient space for walking around the spa. For completion of maintenance works a minimum of 60cm wide inspection pit must be built around the spa. The inspection pit’s bottom must be under the bearing pont of the spa so that water can flow into the pit in case of water leakage. A floor drain or sump pump should be used at the bottom of the pit to ensure continual water drainage. In case of sinking the spa only the portion below the spa’s acrylic edge can be sunk. The air of the inspection pit steams up. To prevent unpleasant odors proper ventilation must be provided (e.g. installing ventilators). The costs of pulling the spa out of the ground are borne by the user. If the aforemen-tioned conditions are not present, setting up the spa may fail.



2. Electrical connection

All the above stated electrical preparation must be ensured by the costumer. Every product has own connection drawing.  
Use only copper wires. Change the fuses always with the same type. The device has to be connected to the equipotential grid.

|  |  |  |  |  |  |   |  |
|--|--|--|--|--|--|---|--|
|  |  |  |  | Product family: <b>SwimLine</b>  |  |   |  |
| Sheet name: <b>INFO(2)</b>   |  |  |  | Projection  |  |  |  |
| File name: <b>FJ_WU00035_ENG_Amazonas-2019_Turbina_úszómedence</b> |  |  |  |  |  |   |  |
| Dimension SPA: <b>2350x5500x1470 mm</b>                            |  | Min. electrical needs: <b>240 V - 35A - 50Hz - 3 kW Heater</b> |  |  |  |   |  |
| 1 person ~75 kg  |  | Weight of the SPA: <b>kg</b>                                   |  | Control box: <b>GECKO YE-3 + K1000</b>   |  |   |  |
| Water disp.: <b>630 kg</b>   |  | Rim height: <b>150 mm</b>                                      |  | Approved by:   |  | Pr. No: <b>P-00182</b><br>Fe. No:   |  |
| Minimum water: <b>8036 liter</b>                                   |  | Created: <b>2019. 09. 27.</b>                                  |  | Drawer: <b>bato.peter - 2019. 09. 27. 10:36:40</b>   |  | Number: <b>WU00035</b>  |  |
|  |  |  |  | A3   |  | M 1:17  |  |
|  |  |  |  |  |  | page 2 / 3  |  |



Product family: **SwimLine**

|  |  |  |   |               |                   |
|--|--|--|---|---------------|-------------------|
| Sheet name: <b>SEMICABINET(2)</b>                                  |  | Projection  | <br>Wellis Magyarország Zrt. |               |                   |
| File name: <b>FJ_WU00035_ENG_Amazonas-2019_Turbina_úszómedence</b> |  |  |   |               |                   |
| Dimension SPA: <b>2350x5500x1470 mm</b>                            | Min. electrical needs: <b>240 V - 35A - 50Hz - 3 kW Heater</b> |  |   |               |                   |
| Weight of the SPA: <b>kg</b>                                       | Control box: <b>GECKO YE-3 + K1000</b>                         |  |   |               |                   |
| Rim height: <b>150 mm</b>  | Approved by:   | Pr. No: <b>P-00182</b><br>Fe. No:  | Number: <b>WU00035</b>  |               |                   |
| Created: <b>2019. 09. 27.</b>                                      | Drawer: <b>bato.peter - 2019. 09. 27. 10:36:40</b>             |  | <b>A3</b>   | <b>M 1:17</b> | <b>page 3 / 3</b> |

File path: >>> C:\WELLIS\_FDM\Project\00182-Swimspa gyártás rendszereleir\WU0000X\_Amazonas\_2019\_turbinai